SATELCOM DVBS/S2 TUNER

SATELCOM WIRELESS

DVBS/S2 Tuner with EtherCAT

World's First DVBS/S2 Tuner

OVERVEIW

World's First Ethercat Communication DVBS/S2 Tuner.

Ethercat is the fastest industrial communication protocol, nearly realtime (less than 100 μs. Cycle time).

Picture

Specifications

Input Voltage	13-30 VDc
Typical Power Consumption	15 watt
Receiving Frequency Range	950 ~ 2150MHz
RF Input Impedance	75Ω
Humidity	Operating: less than 85% Storage: less than 90%
Temperature	Operating: 0℃ to 70℃ Storage: -40℃ to 125℃

	Min/Typ	Max	Unit
Input Level	-65	-25	dBm
RF Input VSWR	2	3	dBm
Noise Figure	6	10	dBm
Gain Deviation 950 ~ 2150 MHz	8	10	dB

Mechanical Specifications

Dimensions	95.50 x 48.70 x 21.50mm
Connector Type	F Type (Female)
Weight	100 gr
Temperature Range	-40 to 125℃
Relative Humidity	up to 90%

Important Notice: Information contained in this data sheet is believed to be reliable at the date of issue, however accuracy and completeness is not guaranteed. Satelcom holds the right to change the product specifications without notice.

DVBS/S2 Tuner with EtherCAT

Technical Drawing & Dimensions

Important Notice: Information contained in this data sheet is believed to be reliable at the date of issue, however accuracy and completeness is not guaranteed. Satelcom holds the right to change the product specifications without notice.